



US009222559B2

(12) **United States Patent**
Nishikawa et al.

(10) **Patent No.:** **US 9,222,559 B2**
(45) **Date of Patent:** **Dec. 29, 2015**

(54) **ELASTIC MOTOR-SPRING ACTUATOR**

H02K 2201/18 (2013.01); *H02K 2207/03*
(2013.01); *Y10T 74/18568* (2015.01); *Y10T*
74/18576 (2015.01)

(75) Inventors: **Kiisa Nishikawa**, Flagstaff, AZ (US);
Theodore A. Uyeno, Valdosta, GA (US)

(58) **Field of Classification Search**
CPC *H02K 7/06-7/075*; *F16H 25/2012*;
F16H 25/2028; *F16H 25/16*
USPC *310/80*; *74/89-89.22*
See application file for complete search history.

(73) Assignee: **Arizona Board of Regents, acting for
and on behalf of Northern Arizona
University**, Flagstaff, AZ (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 1050 days.

(56) **References Cited**

U.S. PATENT DOCUMENTS

(21) Appl. No.: **13/203,185**

4,449,416 A * 5/1984 Huitema 74/336 R
5,249,474 A * 10/1993 Gregory 74/15.66

(22) PCT Filed: **Mar. 8, 2010**

(Continued)

(86) PCT No.: **PCT/US2010/000706**

FOREIGN PATENT DOCUMENTS

§ 371 (c)(1),
(2), (4) Date: **Dec. 2, 2011**

FR 2861154 4/2005
JP 55107080 8/1980

(87) PCT Pub. No.: **WO2010/104566**

OTHER PUBLICATIONS

PCT Pub. Date: **Sep. 16, 2010**

International Search Report for PCT/US2010/000706 dated May 18,
2010.

(65) **Prior Publication Data**

(Continued)

US 2012/0074795 A1 Mar. 29, 2012

Related U.S. Application Data

Primary Examiner — Thomas Truong

(74) *Attorney, Agent, or Firm* — Fennemore Craig, P.C.

(60) Provisional application No. 61/158,563, filed on Mar.
9, 2009.

(57) **ABSTRACT**


(51) **Int. Cl.**
F16H 25/20 (2006.01)
F16H 33/02 (2006.01)

(Continued)

An actuator according to one embodiment of the present invention may include a fixed member and a free member. The free member is operatively engaged with the fixed member so that the free member is moveable with respect to the fixed member. The actuator also includes means for moving the free member with respect to the fixed member. An elastic element operatively associated with the free member and the fixed member is operable to store energy without a change in an overall length of the actuator.

(52) **U.S. Cl.**
CPC *F16H 33/02* (2013.01); *F16H 25/20*
(2013.01); *H02K 7/00* (2013.01); *H02K 41/031*
(2013.01); *F16H 25/2204* (2013.01); *F16H*
2025/2059 (2013.01); *H02K 21/046* (2013.01);

18 Claims, 9 Drawing Sheets



- (51) **Int. Cl.**
H02K 7/00 (2006.01)
H02K 41/03 (2006.01)
F16H 25/22 (2006.01)
H02K 21/04 (2006.01)

2009/0229846 A1 9/2009 Kawano et al.
 2009/0320463 A1 12/2009 Jansen

OTHER PUBLICATIONS

Written Opinion of the International Searching Authority for PCT/US2010/000706 dated May 18, 2010.

European Search Report dated Jun. 26, 2012 from European Application No. 10751117.2 (15pp).

Hurst, Jonathan W., et al., "An Actuator with Physically Variable Stiffness for Highly Dynamic Legged Locomotion," Proceeding of the 2004 IEEE International Conference on Robotics & Automation, New Orleans, LA, Apr. 2004, pp. 4662-4667.



Park, Hae-Won, et al., "Identification of a Bipedal Robot with a Compliant Drivetrain (Parameter Estimation for Control Design)," IEEE Control Systems Magazine, Apr. 2011, pp. 63-88, [Digital Object Identifier 10.1109/MCS.2010.939963, date of publication: Mar. 16, 2011].

* cited by examiner

- (56) **References Cited**

U.S. PATENT DOCUMENTS

5,720,202 A 2/1998 Senjo et al.
 6,003,403 A 12/1999 Klippert et al.
 6,234,034 B1 5/2001 Ando
 2002/0047367 A1 4/2002 Kim et al.
 2005/0269893 A1 12/2005 Fujimoto
 2006/0169081 A1 8/2006 Betson
 2008/0051942 A1 2/2008 Smith et al.
 2008/0134807 A1 6/2008 May
 2008/0271552 A1 11/2008 Arenz et al.






FIG.3




FIG.4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG.9




FIG. 10




FIG.11a

FIG.11b

FIG.11c

ELASTIC MOTOR-SPRING ACTUATOR**CROSS-REFERENCE TO RELATED APPLICATION**

This application is the U.S. national stage of PCT/US2010/000706, filed on Mar. 8, 2010, which claims the benefit of U.S. Provisional Application No. 61/158,563, filed Mar. 9, 2009 which are hereby incorporated by reference for all that they disclose.

CONTRACTUAL ORIGIN OF THE INVENTION

Financial assistance for this project was provided by the United States Government, NSF Numbers IBN-9809942, IBN-0215438, IBN-0240349, IOS-0623791, IOS-0732949; and the United States Government may own certain rights to this invention.

TECHNICAL FIELD

This invention relates to actuator systems in general and more particularly to actuators that simulate biological muscle contraction.

BACKGROUND ART

Generally speaking, an actuator is a mechanical device or system that is used to control another mechanical device or system. Most actuators take energy, typically in the form of a pressurized fluid (e.g., for pneumatic and hydraulic actuators) or electricity (e.g., for electric motors and solenoids) and convert it into mechanical motion that can be used to control or move the mechanical device or system.

While it is possible to design such actuators to have any of a wide range of operating characteristics and responses, it has proven considerably more difficult to design actuators that can faithfully reproduce or simulate the behavior of biological muscle contractions. For example, muscular motion in both humans and animals is dependent upon the storage of energy and the interaction of certain proteins upon stimulation by chemical entities such as calcium. The classical model of muscular movement is known as the "sliding filament theory." However, this theory does not explain extremely rapid muscular movement such as a toad using the tongue to capture an insect, which is a near instantaneous muscle movement. Actuators that can more closely simulate or replicate biological muscle contractions could be used to advantage in a wide range of fields and applications, including the fields of robotics and prosthetics.

DISCLOSURE OF THE INVENTION

An actuator according to one embodiment of the present invention may include a fixed member and a free member. The free member is operatively engaged with the fixed member so that the free member is moveable with respect to the fixed member. The actuator also includes means for moving the free member with respect to the fixed member. An elastic element operatively associated with the free member and the fixed member is operable to store energy without a change in an overall length of the actuator.

Another embodiment of an actuator according to the present invention may include a fixed member and a connector member. The connector member is operatively engaged with the fixed member so that the connector member can move with respect to the fixed member. A free member is

operatively engaged with the connector member so that the free member can move with respect to the fixed member. A drive system operatively associated with the fixed member and the connector member is operable to move the connector member with respect to the fixed member. A first end of an elastic element is connected to the free member, whereas a second end of the elastic element is connected to said connector member.

Another embodiment of an actuator according to the present invention may include a housing and a plurality of electromagnets positioned around the housing so that the electromagnets define at least one generally helical path. A rotor head mounted for rotation and translation within the housing includes at least one magnet mounted thereon and an output shaft mounted thereto. A spring attached to the rotor head is selectively engageable and disengageable with the housing. A control system operatively associated with the plurality of electromagnets selectively activates the electromagnets.

BRIEF DESCRIPTION OF THE DRAWINGS

Illustrative and presently preferred embodiments of the invention are shown in the accompanying drawing in which:

Illustrative and presently preferred embodiment of the invention are shown in the accompanying drawings in which:

FIG. 1 is a plan view of a first embodiment of an actuator according to the present invention;

FIG. 2 is a plan view of the actuator illustrated in FIG. 1 with a portion of the free member broken away to show the elastic element;

FIG. 3 is an exploded perspective view of the first embodiment of the actuator showing the various components thereof;

FIG. 4 is an exploded sectional view in elevation of the actuator components illustrated in FIG. 3;

FIG. 5 is a perspective view of an adjustable elastic element that may be substituted for the elastic element illustrated in FIGS. 1-4;

FIG. 6 is a perspective view of a second embodiment of an actuator according to the present invention showing the placement of external electromagnets along helical paths;

FIG. 7 is a side view in elevation of the actuator illustrated in FIG. 6;

FIG. 8 is an end view of the actuator showing the arrangement of the rotor head magnets and external electromagnets;

FIG. 9 is an enlarged end view of a portion of the rotor head showing the relative orientations of the magnetic fields of one rotor head magnet and a pair of external electromagnets;

FIG. 10 is an enlarged perspective view of the actuator illustrated in FIG. 6 more clearly showing the catch for enabling and disabling spring rotation; and

FIGS. 11(a-c) show the actuator in three different positions, a contracted position, an intermediate position, and an extended position, respectively.

BEST MODE FOR CARRYING OUT THE INVENTION

A first embodiment 10 of an elastic motor-spring actuator according to the present invention is illustrated in FIGS. 1-4 and may comprise a fixed member 12 and a free member 14. The fixed and free members 12 and 14 are operatively connected together so that the free member 14 is moveable with respect to the fixed member 12. In the embodiment 10 shown in FIGS. 1-4, the fixed and free members 12 and 14 are operatively connected together by a connector member 16. Alternatively, the fixed and free members 12 and 14 can be

operatively connected together without a connector member **16**, such as, for example, as in the case of a second embodiment **210**, illustrated in FIGS. **6-11**.

The actuator **10** may also comprise an elastic element **18** that is operatively associated with the fixed and free members **12** and **14**, as best seen in FIG. **2**. In the first embodiment **10**, the elastic element **18** is connected to the fixed member **14** via the connector member **16**. Alternatively, other arrangements, such as the arrangement of the second embodiment **210**, are also possible for operatively connecting the fixed and free members **12** and **14** with an elastic element **18**.

As will be described in much greater detail herein, elastic element **18** provides actuator **10** with a degree of compliance or springiness. In certain embodiments, the degree of compliance can be changed or tuned as may be desired for the particular application. In addition, the compliance of actuator **10** may be changed or varied depending on the degree of force that is provided on (or exerted by) actuator **10**. In one embodiment, elastic element **18** may comprise a trapezoidal configuration, as best seen in FIGS. **2** and **3**. The trapezoidal configuration causes the elastic element **18** to elongate non-linearly in response to a given force, thereby providing the actuator **10** with a non-linear compliance. Alternatively, other configurations for elastic element **18** are possible and may be used to provide actuator **10** with any of a wide range of compliance characteristics.

Actuator **10** may also comprise a drive system **20** that is operatively associated with the fixed and free members **12** and **14**. Drive system **20** provides a means for moving the free member **14** with respect to the fixed member **12** and may comprise a variety of components and elements suitable for providing this function. By way of example, in the embodiment **10** illustrated in FIGS. **1-4**, drive system **20** may comprise a motor **22** mounted to fixed member **12**. Motor **22** is operatively connected to a lead screw **24**. A nut **26** mounted to connector member **16** engages lead screw **24**. Rotation of lead screw **24** by motor **22** causes nut **26**, thus connector member **16**, to move or translate along a longitudinal axis **28** of actuator **10**, i.e., generally in the directions indicated by arrows **30** and **31**. See FIGS. **1** and **2**.

The fixed and free members **12** and **14** of actuator **10** also may be configured to attach to the particular load that is to be acted on by actuator **10**. For example, in the embodiment illustrated in FIGS. **1-4**, actuator **10** may be provided with respective mounting lugs or rings **32** and **34** to allow the actuator **10** to be operatively connected to a load, i.e., moveable device or object **36**, that is to be acted on by actuator **10**. For example, in one example configuration, first ring **32** may be attached or connected to a fixed object **38**, whereas second ring **34** may be attached or connected to the moveable object **36**.

Actuator **10** may be operated as follows to act on a load, such as an object **36** attached to ring **34**. Generally speaking, actuator **10** will be used to provide a pulling or contraction force (i.e., a force in the direction of arrow **30**) to the moveable object **36**, although the actuator **10** may also be used to provide an extension force (i.e., in the direction of arrow **31**). Depending on the relative initial position of the moveable object **36**, as well as on the initial length of actuator **10**, elastic element **18** may be slightly stretched or elongated at an initial condition. That is, the actuator **10** may be pre-loaded, applying a slight contractile force to the moveable object **36**.

Additional contractile force can be applied to the object **36** by operating the drive system **20**. More specifically, motor **22** will rotate the lead screw **24** in a direction that will cause the nut **26** (FIGS. **3** and **4**) to move in direction **30**. The movement of nut **26** will cause the connector member **16** and free mem-

ber **14** to move in direction **30** as well. As the connector member **16** moves in direction **30**, it pulls on free member **14** via elastic element **18**. Elastic element **18** extends or stretches until the force exerted on elastic element **18** equals the resistance offered by the object **36**. Thereafter, moveable object **36** will move in direction **30**.

In addition to the application of a contraction force, i.e., a force in the direction of arrow **30**, actuator **10** may be operated to apply to object **36** an extension force, i.e., a force in the direction of arrow **31**. Application of the extension force may be accomplished by reversing the direction of motor **22**. To the extent that elastic element **18** is stretched or elongated during the contraction cycle, movement of the actuator **10** in the extension direction **31** will be assisted by the energy stored in elastic element **18**. If the elastic element **18** becomes fully relaxed, continued rotation of lead screw **24** will cause the connector module **16** to continue to move in direction of arrow **31**, until pins **60** and **62** contact the ends of respective slots **56** and **58**. At this point, continued movement of connector module **16** will result in corresponding movement of free member **14** in the direction of arrow **31**.

A significant advantage of the present invention is that it may be operated in a manner that closely simulates biological muscle contraction. Consequently, actuators according to the present invention may be used to advantage in a wide range of fields and applications, including the fields of robotics and prosthetics. More particularly, actuators of the present invention may be operated in accordance with a "winding filament" or "winding spring" model for how the protein titin contributes to biological muscle contraction. Stated another way, an actuator made in accordance with the teachings of the present invention does not function simply as a linear motor, but includes an elastic energy storage element as well. The elastic element is capable of changing its compliance automatically in order to maximize the work done by the actuator. That is, not only can the drive system do work on the elastic element, but the elastic element may do work on the drive system, speeding the return or recoil of the actuator.

Moreover, and like the titin model, the actuator of the present invention is capable of storing elastic energy without a change in overall length of the actuator. In addition, the change in length and compliance of the actuator is tunable and further these characteristics (i.e., length and compliance) may differ depending on whether the actuator is shortening or contracting while energized or passively recoiling due to the return of elastic energy from the elastic element. The elastic element exhibits recoil during fast unloading and exhibits a tuneable non-linear relationship between the magnitude of the load and the compliance of the actuator. The overall characteristics of the actuator are such that the actuator becomes less compliant with stronger contraction forces and more compliant with weaker contraction forces.

Having briefly described one embodiment of the actuator according to the present invention, as well as some of its more significant features and advantages, various exemplary embodiments of actuators according to the present invention will now be described in detail. However, before proceeding with the detailed description, it should be noted that, while the various embodiments are shown and described herein as they might be used in certain operational scenarios to act on and move object **36** with respect to another object **38**, actuators according to the present invention may be used in a wide range of applications and in a wide range of operational scenarios, as would become apparent to persons having ordinary skill in the art after having become familiar with the teachings provided herein. Consequently, the present inven-

5

tion should not be regarded as limited to the particular embodiments, devices, and operational scenarios shown and described herein.

Referring back now to FIG. 1, a first embodiment 10 of actuator according to the present invention may comprise a fixed or contractile module 12 and a free or compliant module 14. A connector member or module 16 operatively connects the contractile and compliant modules 12 and 14 together so that the compliant module 14 can move with respect to the contractile module 12.

Before proceeding with the description, it should be noted that, as used herein, the terms “fixed” and “free” are used for convenience in referring to those components of the actuator that, in the embodiments described herein, are generally “fixed” and “free” during normal actuator operation. That is, in a typical application, the fixed member 12 of actuator 10 is attached to an object or device that will remain stationary during actuator operation, whereas the free member 14 will be attached to an object or device that is to be moved (or acted on) by actuator 10. However, in an alternative arrangement, the free member 14 of actuator 10 could be connected to a “fixed” (i.e., immovable) object, in which case it could be referred to in such an alternative arrangement as the “fixed” member. In still another arrangement, both ends of actuator 10 could be connected to moveable objects, i.e., both ends of actuator 10 may move relative to some arbitrary fixed reference frame.

However, because persons having ordinary skill in the art would appreciate this difference and would readily understand that the fixed and free members 12 and 14 of actuator 10 may not necessarily be “fixed” and “free” in any particular application, the following description will continue to use the terms “fixed” and “free” as a matter of convenience without being limited to whether the fixed and free members 12 and 14 are truly “fixed” and “free” in a particular actuator application.

Continuing now with the description, in the embodiment shown and described herein, the fixed member 12 may comprise a generally elongate, tubular structure having a proximal end 40 and a distal end 42 that is sized to slidably receive the connector member or module 16, as best seen in FIGS. 1 and 2. Because the fixed member 12 generates the forces for contraction and elongation, i.e., forces in the directions of arrows 30 and 31, respectively, via rotation of lead screw 24, it may be referred to herein in the alternative as “contractile module” 12.

Contractile module 12 may be provided with a pair of elongated slots 44 and 46, as best seen in FIG. 4. Elongated slots 44 and 46 are sized to slidably receive respective pins 48 and 50 provided on a first end 64 of connector member 16. See FIGS. 1, 2, and 4. The engagement of the pins 48 and 50 with respective slots 44 and 46 allows the connector member 16 to slide back and forth along axis 28, i.e., generally in the directions of arrows 30 and 31, as best seen in FIGS. 1 and 2. The engagement of pins 48 and 50 with slots 44 and 46 limits the axial movement or travel of the connector module 16 and also prevents the connector member 16 from rotating with respect to contractile module 12. Distal end 42 of contractile module 12 may be configured to receive the motor 22 and lead screw 24 of drive system 20 in the manner that will be described in greater detail below.

Contractile module 12 may be fabricated from any of a wide range of materials (e.g., metals or plastics) that are now known in the art or that may be developed in the future that are, or would be, suitable for use in the intended application. Consequently, the present invention should not be regarded as limited to a contractile module fabricated from any particular

6

material. However, by way of example, in one embodiment, contractile module 12 is fabricated from acrylic plastic. In another embodiment, the contractile module 12 is fabricated from brass.

Free member 14 is similar in certain respects to the fixed member 12 and may also comprise a generally elongate, tubular structure having a proximal end 52 and a distal end 54, as best seen in FIGS. 1-4. As was the case for fixed member 12, free member 14 is also sized or configured to slidably receive connector member or module 16. Because free member 14 provides the compliance, recoil, and elasticity functions of actuator 10, free member 14 also may be referred to herein in the alternative as “compliant module” 14.

Compliant module 14 also may be provided with a pair of elongated slots 56 and 58 therein that are sized to receive respective pins 60 and 62 provided on a second end 66 of connector member 16. The engagement of the pins 60 and 62 with respective slots 56 and 58 allows compliant module 14 to slide back and forth along axis 28, generally in the directions of arrows 30 and 31. The engagement of pins 60, 62 and slots 56, 58 limits the travel or movement of connector module 16 with respect to compliant module 14 and also prevents the compliant module 14 from rotating with respect to connector member 16. In one embodiment, distal end 54 of compliant module 14 may be sized to receive an end cap 55. End cap 55 may be configured to receive ring 34 suitable for engaging the load or object 36. Alternatively, other structures and arrangements may be used to operatively connect the compliant module 14 to the load or object 36, as would become apparent to persons having ordinary skill in the art after having become familiar with the teachings provided herein. Consequently, the present invention should not be regarded as limited to any particular arrangement or structure for connecting the actuator 10 to the load.

Compliant module 14 also may be fabricated from any of a wide range of materials (e.g., metals or plastics) now known in the art or that may be developed in the future that are, or would be, suitable for use in the intended application. Consequently, the present invention should not be regarded as limited to any particular material. However, by way of example, in one embodiment, compliant module 14 is fabricated from brass, although other materials, such as acrylic plastic, may be used as well.

Connector member or module 16 may comprise a generally elongate, tubular structure that is sized to be slidably received by the contractile and compliant modules 12 and 14 in the manner described above. In the particular exemplary embodiment shown and described herein, connector member or module 16 is sized to be received by the contractile and compliant modules 12 and 14 in the manner illustrated in FIGS. 1 and 2. That is, connector module 16 is sized to fit inside the contractile and compliant modules 12 and 14. Alternatively, other arrangements are possible. For example, in another embodiment, connector member 16 may be sized to receive the contractile and compliant modules. That is, connector member 16 may fit or slide over the contractile and compliant modules 12 and 14. In still another alternative arrangement, the various modules 12, 14, and 16 could comprise a “telescoping” type of arrangement, wherein the connector module 16 fits inside the contractile module 12, and wherein the compliant module 14 fits inside connector module 14, or vice-versa.

Referring now primarily to FIGS. 3 and 4, a first end 64 of connector member 16 is sized to receive nut 26. As described herein, nut 26 operatively engages the lead screw 24 provided within contractile module 12. The first end 64 of connector member 16 may also be provided with a pair of pins 48 and 50

that are configured to slidably engage the slots **44** and **46** provided in contractile module **12** in the manner already described. Alternatively, pins **48** and **50** could be provided on nut **26**, as would become apparent to persons having ordinary skill in the art after having become familiar with the teachings provided herein. Accordingly, the present invention should not be regarded as limited to the particular arrangement of nut **26** and pins **48** and **50** shown and described herein.

Second end **66** of connector member **16** may be provided with an end cap **68**, as best seen in FIG. 4. End cap **68** may be provided with a pair of pins **60**, **62** that are configured to slidably engage the slots **56** and **58** provided on compliant module **14**, in the manner already described. Alternatively, pins **60** and **62** could be otherwise provided on second end **66** of connector member **16**. In addition, end cap **68** may also be provided with a suitable attachment structure or mounting lug (not shown) to allow elastic element **18** to be secured to connector member **16**. See FIG. 2. Alternatively, elastic element **18** could be secured to end cap **68** by means of an adhesive.

As was the case for the contractile and compliant modules **12** and **14**, connector member **16** may be fabricated from any of a wide range of materials, such as metals or plastics, that are now known in the art or that may be developed in the future that are, or would be, suitable for use in the intended application. Consequently, the present invention should not be regarded as limited to any particular material. However, by way of example, in one embodiment, connector member **16** is fabricated from aluminum. End cap **68** may likewise be fabricated from any of a wide range of materials suitable for the intended application. By way of example, in one embodiment, end cap **68** is fabricated from acrylic plastic. Alternatively, other materials could be used, as would become apparent to persons having ordinary skill in the art after having become familiar with the teachings provided herein.

Actuator **10** may also comprise an elastic element **18**. As briefly described above, elastic element **18** provides the actuator **10** with compliance or springiness and also serves as an energy storage element. That is, and as will be described in greater detail below, the drive system **20** can do work on (i.e., store energy in) elastic element **18** while the actuator **10** is contracting (e.g., during a contraction cycle). In addition, the elastic element **18** can also do work on (i.e., return energy to) the drive system **20** while the actuator **10** is extending (e.g., during an extension cycle). Elastic element **18** may be configured to provide the actuator **10** with any of a wide range of compliance properties or “schedules,” depending on the particular materials, shapes, and configurations of elastic element **18**.

For example, and with reference now primarily to FIGS. 2 and 3, in one embodiment, elastic element **18** may comprise an elastic material having non-linear elongation properties. More particularly, elastic member **18** may comprise a thin, sheet-like member having a trapezoidal configuration wherein a first end **70** has a smaller dimension or is shorter than a second end **72**. The trapezoidal configuration of elastic element **18** causes the elastic element **18** to elongate or stretch in a non-linear manner with a given force. The non-linear response of the elastic element **18** causes the compliance of the actuator **10** to vary depending on the contractile force that is applied by the actuator **10**. In the particular embodiment shown and described herein, the actuator **10** will become less compliant with increased contraction forces and more compliant with decreased contraction forces.

The specific dimensions of the elastic element **18**, as well as the particular material from which it may be fabricated, may be varied depending on a wide range of factors, including

the particular degree of compliance and compliance variation (i.e., non-linear response) that may be required or desired in the particular application. Consequently, the present invention should not be regarded as limited to elastic elements fabricated from any particular material or having any particular dimensions. However, by way of example, in one embodiment, the elastic element **18** may comprise latex having a thickness **74** (FIG. 4) of about 0.2 mm (about 0.008 inches) and an overall length **76** of about 25 mm (about 1 inch). The length of short end **70** is about 5 mm (about 0.2 inches), whereas the length of long end **72** is about 10 mm (about 0.4 inches).

As described herein, the elastic element **18** may comprise any of a wide range of materials having any of a wide range of configurations or shapes to provide the actuator **10** with any of a wide range of compliance characteristics. An elastic element **18** comprising the trapezoidal configuration illustrated in FIGS. 2-4 is one example of an elastic element **18** that may be used. However, other arrangements and configurations are possible. For example, another embodiment may comprise an adjustable elastic element **118**. Adjustable elastic element **118** may be used or implemented to provide the actuator **10** with adjustable compliance characteristics. In addition, the adjustable elastic element **118** will allow the compliance of the actuator **10** to be adjusted “on-the-fly,” i.e., during actuator operation, as will be described in greater detail below.

Referring now primarily to FIG. 5, in another embodiment, adjustable elastic element **118** may comprise a take-up system **117** that may be used to lengthen and shorten an operating length **119** of the elastic element **118**. Changing the operating length **119** of elastic element **118** will change the compliance of actuator **10**. Depending on the application, the take-up system **117** may be operated before the actuator **10** is operated to provide actuator **10** with a desired degree of compliance. Alternatively, the take-up system **117** may be operated on-the-fly, i.e., during actuator operation, to dynamically change the compliance of actuator **10** during operation.

In the particular embodiment illustrated in FIG. 5, take-up system **117** may be mounted to the distal end **54** (FIGS. 1 and 2) of compliant module **14**. Take-up system **117** may comprise a spool **121** operatively connected to a drive motor **123**, such as, for example, via a transmission assembly **125**. A control system **127** operatively connected to drive motor **123** may be used to operate drive motor **123**. Drive motor **123** may be used to rotate spool **121** about axis **129** to change the operating length **119** (i.e., the operating length **119** refers to the relaxed or unstretched length of that portion of the elastic element **118** extending between spool **121** and end cap **68**, not the distance between spool **121** and end cap **68** of connector module **16**) of elastic element **118**. Shorter operating lengths **119** of elastic element **118** will reduce the compliance of actuator **10**, whereas longer operating lengths **119** will increase the compliance of actuator **10**.

The various devices and components comprising take-up system **117** may comprise any of a wide range of components and devices that are now known in the art or that may be developed in the future that are (or would be) suitable for the intended application. Consequently, the present invention should not be regarded as limited to any particular components and devices. However, by way of example, in one embodiment, elastic element **118** may comprise an elastic cord fabricated from nylon-reinforced rubber and having a constant cross-section. Spool **121** may be fabricated from plastic, and motor **123** may comprise a stepper motor. Transmission system **125** may comprise a spur-gear transmission system. Control system **127** may comprise an electronic

motor control system suitable for controlling the particular type of motor **123** that is to be used and that is suitable for providing the desired control functionality. Consequently, the present invention should not be regarded as limited to any particular type of motor control system **127**. However, by way of example, in one embodiment, motor control system **127** comprises a stepper motor control system capable of reversibly driving stepper motor **123** in the clockwise and counterclockwise directions.

Referring back now primarily to FIGS. **1** and **4**, the actuator **10** may also be provided with a drive system **20** for providing a means for moving the free member or compliant module **14** with respect to fixed member or contractile module **12**. In the embodiment illustrated in FIGS. **1-4**, drive system **20** may comprise a motor **22**, a lead screw **24**, a nut **26**, and a control system **78**. Motor **22** may be mounted to the distal end **42** of contractile module **12**. Lead screw **24** is operatively connected to motor **22** so that motor **22** may turn or rotate lead screw **24** in the clockwise and counterclockwise directions. In the embodiment shown and described herein, lead screw **24** is mounted to motor **22** and is driven thereby by an integral transmission assembly. Alternatively, other arrangements are possible, as would become apparent to persons having ordinary skill in the art after having become familiar with the teachings provided herein. Consequently, the present invention should not be regarded as limited to the particular configuration shown and described herein.

Motor **22** may comprise any of a wide variety of motors, such as brushed or brushless dc motors, now known in the art or that may be developed in the future that are or would be suitable for the particular application. Consequently, the present invention should not be regarded as limited to any particular motor type. However, by way of example, in one embodiment, motor **22** comprises a high-speed brushed dc motor of the type well-known in the art and readily commercially available.

Lead screw **24** may comprise any of a wide variety of lead screws that are well-known in the art and that are readily commercially available. The pitch and diameter of the lead screw **24** may be selected to provide the actuator **10** with the desired speed and/or force development (i.e., mechanical advantage) characteristics, as would become apparent to persons having ordinary skill in the art after having become familiar with the teachings provided herein. By way of example, in one embodiment, lead screw **24** has a pitch of about 0.0625 mm (about 0.0025 inches) and a diameter of about 2.2 mm (about 0.09 inches). Lead screw may be fabricated from any of a wide range of materials, as would become apparent to persons having ordinary skill in the art. By way of example, in one embodiment, lead screw **24** is fabricated from steel.

As described above, connector module **16** is provided with a nut **26** that is configured to operatively engage lead screw **24**. Accordingly, rotation of lead screw **24** will cause nut **26** to move back and forth along lead screw **24** in the directions indicated by arrows **30** and **31**. Nut **26** is mounted to first end **64** of connector module **16** so that movement of the nut **26** along lead screw **24** results in corresponding movement of connector module **16** with respect to contractile module **12**. Nut **26** may be provided with a pair of pins **48** and **50** that are sized to be slidably received by slots **44** and **46** provided in contractile module **12** in the manner already described. Alternatively, other arrangements are possible for mounting the nut **26** to the first end **64** of connector module **16**. Nut **26** may be fabricated from any of a wide range of materials suitable for the intended application and the particular material used for lead screw **24**. Consequently, the present invention should

not be regarded as limited to any particular materials. However, by way of example, in one embodiment, nut **26** is fabricated from steel.

In the embodiment shown and described herein, nut **26** comprises a plain threaded nut sized to operative engage lead screw **24** in the manner described herein. However, other variations are possible. For example, in another embodiment, nut **26** may comprise a ball nut assembly (not shown) wherein balls retained in the nut engage the threads on the lead screw **24**. Generally speaking, ball nuts provide for a longer-wearing and lower friction engagement with a lead screw.

Motor control system **78** controls motor **22**, thus the overall operation of actuator **10**. That is, motor control system **78** may be used to operate actuator **10** to provide contraction and extension forces (i.e., in the directions of arrows **30** and **31**, respectively), as well as to control the speed at which the actuator **10** operates.

Motor control system **78** may comprise an open-loop (i.e., without position feedback) or a closed-loop (i.e., with position feedback) control system, in which the motor **22** is controlled either with or without information relating to the kinematic parameters (i.e., position, velocity, and/or acceleration) of the nut **26**, thus connector module **16**. Generally speaking, it will be desirable to utilize a closed-loop motor control system **78**. Information regarding the position of the connector module **16** may be provided by a linear encoder (not shown) operatively associated with the connector module **16**. Alternatively, a rotary encoder (also not shown) mounted to the motor shaft or lead screw **24** may be used to derive information about the position of the connector module **16**. In still another arrangement, motor control system **78** could sense the voltage and or current provided to motor **22** to derive information regarding the kinematic parameters of connector module **16**. Travel limits (e.g., when the pins reach the ends of their respective slots) can be derived by detecting the increased current requirements of motor **22** when actuator **10** reaches the travel limits.

Motor control system **78** may also be configured to control the motor **22** based in part on the strain on actuator **10**. In such a configuration, the actuator **10** may be provided with a load cell or strain gauge **80** capable of measuring the strain in the actuator. The load cell or strain gauge **80** may be operatively connected to motor control system **78** which may thereafter control the motor **22** based in part on the measured strain. The strain detected by load cell may also be used to determine the stress in the actuator **10**, as would become apparent to persons having ordinary skill in the art.

In one embodiment, the motor control system **78** comprises a closed-loop motor control system that produces a pulse-width-modulated (PWM) signal for causing motor **22** to rotate in the desired direction and at the desired speed. However, because motor control systems suitable for controlling motor **22** are well-known in the art and could be readily provided by persons having ordinary skill in the art after having become familiar with the teachings provided herein, the particular motor control system **78** that may be utilized in one embodiment of the present invention will not be described in further detail herein.

Actuator **10** may be operated as follows to apply a contractile and/or extensive forces to a load or object **36**. As mentioned above, in most applications, actuator **10** will be operated primarily to provide contractile forces to closely simulate biological muscle contraction. As such, the load (e.g., moveable object **36**) connected to actuator **10** will be biased in the extended position. That is, the load or object **36** will tend to return to its initial position once the contractile force applied by actuator **10** is removed. Alternatively, the

11

actuator **10** may be operated to apply an extension force (i.e., in the direction of arrow **31**) as well.

In an exemplary application wherein the actuator **10** is to be operated in a manner to simulate biological muscle contraction, the actuator **10** will be pre-loaded. That is, when the object **36** is located at some initial position, the elastic element **18** will be elongated slightly, and will apply a slight contractile force to the object **36**.

Additional contractile force can be applied to the object **36** by operating control system **78** as necessary to move the actuator **10** in the contractile direction (i.e., in the direction of arrow **30**). High speed rotation of motor **22** will result in the rapid contraction of actuator **10**, whereas lower speed rotation of motor **22** will result in a lower contraction rate. More specifically, when operated in a contraction mode, motor **22** will rotate the lead screw **24** in a direction that will cause the nut **26** (FIGS. **3** and **4**) to move in direction **30**. The movement of nut **26** will cause the connector member **16** and free member **14** to move in direction **30** as well. As the connector member **16** moves in direction **30**, it pulls on free member **14** via elastic element **18**. Elastic element **18** extends or stretches until the force exerted on elastic element **18** equals the resistance offered by the object **36**. Thereafter, moveable object **36** will move in direction **30**.

In an embodiment wherein the elastic element **18** is nonlinear, i.e., wherein the elastic element **18** comprises the trapezoidal configuration illustrated in FIGS. **2** and **3**, the compliance of actuator **10** will decrease (i.e., become less compliant) with increased contraction forces. Conversely, the compliance of actuator **10** will increase (i.e., become more compliant) with decreased contraction forces. As discussed herein, the inverse relationship between compliance and contraction force is consistent with the titin model of biological muscle contraction.

Moreover, the compliance of the actuator **10** may be selected or "tuned" to a particular application by providing the elastic element with the appropriate shape and/or configuration. Alternatively, if the actuator **10** is provided with an adjustable elastic element **118**, as illustrated in FIG. **5**, then the compliance of actuator **10** can not only be easily tuned for a particular application (e.g., by operating the control system **127** to change the operating length **119** of elastic element **118**), but can also be tuned or changed on-the-fly, i.e., when the actuator **10** is being operated. Thus, appropriate operation of the adjustable elastic element **118** can be used to cause actuator **10** to more closely simulate or mimic the dynamics of biological muscle contraction.

In addition to the operation of the actuator **10** in a contraction phase, described above, actuator **10** may also be operated in an extension phase. Operation in the extension phase may be conducted to allow the object **36** to return to the initial position, i.e., by reducing the contraction force below the return bias. Alternatively, operation in the extension phase may be conducted so as to cause actuator **10** to apply to object **10** an extension force, i.e., a force in the direction of arrow **31**. Operation of actuator **10** in the extension phase may be accomplished by reversing the direction of motor **22**. To the extent that elastic element **18** is stretched or elongated during the contraction phase, movement of the actuator **10** in the extension phase will be assisted by the energy stored in elastic element **18**. That is, elastic element **18** will do work on drive system **20**, thereby returning to the system energy stored in elastic element **18** during the contraction phase. If the elastic element **18** becomes fully relaxed, continued rotation of lead screw **24** will cause the connector module **16** to continue to move in direction of arrow **31**, until pins **60** and **62** contact the ends of respective slots **56** and **58**, at which point continued

12

movement of connector module **16** will result in corresponding movement of free member **14** in the direction of arrow **31**.

Another embodiment **210** of an actuator according to the present invention is best seen in FIGS. **6-11** and may comprise a hollow cylindrical casing or housing **212** having a cap **214** at its fixed end **216** and a base **218** at its free end **220**. Base **230** may also be provided with a central aperture or opening therein (not shown) sized to slidably receive a rotor shaft **230**. A central guide member or rod **222** extends along the length of the cylindrical housing **212**, i.e., between the fixed end **216** and the free end **220**, as best seen in FIGS. **6** and **7**. More specifically, distal end **224** of guide member or rod **222** may be attached to the cap **214**, whereas proximal end **226** of guide rod **222** may be substantially supported within a central bore **228** of rotor shaft **230**, as best seen in FIG. **7**. Thus, in this embodiment **210**, the fixed member is the housing **212**, whereas the free member is the rotor shaft **230**.

Actuator **210** may also be provided with a plurality of electromagnets **232** mounted around the outer periphery **234** of cylindrical housing **212** along one or more helical paths or tracks **236**. In the embodiment shown and described herein, the various electromagnets **232** are arranged around the outer periphery **234** of housing **212** along three (3) separate helical paths or tracks **236**. Such a configuration allows the electromagnets **232** to be mounted at six positions or locations around the housing **212**, as best seen in FIG. **8**. Alternatively, the various electromagnets **232** may be mounted around housing **212** along a greater or lesser number of helical paths **236**.

In the embodiment shown and described herein wherein the various electromagnets **232** are mounted along three separate helical paths **236**, the various electromagnets **232** may be positioned around the outer periphery **234** of housing **212** at intervals of about 60° , as best seen in FIG. **8**. This arrangement is geometrically efficient and represents the fewest number of electromagnets **232** needed to generate magnetic fields capable of covering the largest possible rotor assembly **244**, thereby improving the rotational momentum of the rotor assembly **244**. The minimum number of electromagnets **232** required for each 360° of helical track **236** is six (6). A larger number of electromagnets **232** per 360° of helical track **236** could be used and may provide better rotational resolution (i.e. the shaft **230** could complete a rotation of 360 degrees in a larger number of discrete steps).

Each electromagnet **232** may comprise a plurality of windings or coils **238** that are wrapped around a core **240**. The various electromagnets **232** are oriented such that the axis **242** of each electromagnet **232** is generally perpendicular to the tangent of the curvature of the helical path **236**, as best seen in FIG. **9**. This arrangement allows the magnetic field vector **B** to point toward or away from the central guide member **222** of actuator **212**, depending on the polarity of the voltage that is applied to the windings **238**.

The various electromagnets **232** may be identical to one another, having the same number of windings **238**, wound in the same direction, and around the same type of core **240**. By way of example, core **240** may comprise a ferrite material. Alternatively, the core may comprise air. The windings or coils **238** may be a single layer or more preferably multiple layers of insulated wire.

Referring back now primarily to FIGS. **6-8**, actuator **210** may also comprise a rotor assembly **244** having a head **246** that is sized to be slidably received by cylindrical housing **212**. Head **246** is also provided with a central opening **248** (FIG. **8**) therein sized to slidably receive the central guide member **222**. The rotor shaft **230** is fixedly attached to head **246** and is generally aligned with the central opening **248**

provided in head 246 so that the central opening 248 is generally aligned with the central bore 228 of rotor shaft 230. See also FIG. 7. Thus, the rotor head 246 and shaft 230 may slide along guide member 222, e.g., generally between the retracted and extended positions illustrated in FIGS. 11(a) and 11(c). The arrangement also supports the proximal end 226 of guide member 222, as best seen in FIG. 7.

The head 246 of rotor assembly 244 may also be provided with a plurality of magnets 250 that are mounted thereto at generally evenly spaced locations around the head 246, as best seen in FIG. 8. The various magnets 250 provided on the head 246 of rotor assembly 244 may all be oriented in generally the same direction, e.g., so that the magnetic field vectors B of each magnet 250 are oriented generally outwardly, as best seen in FIGS. 8 and 9. Alternatively, the various magnets 250 could be arranged so that their north poles face generally inwardly (i.e., so that the magnetic field vector B of each magnet 250 would point generally inwardly, toward the guide member 222).

Generally speaking, the relationship between the number of magnets 250 and the number of helical tracks 236 should be 1:1. That is, head 246 should be provided with the same number of magnets 250 as there are helical tracks 236. Alternatively, there may be a benefit to having multiple helical tracks 236 per magnet 250 if the number of electromagnets 232 per 360° of helical track 236 differs from the number provided in the exemplary embodiment. Such an arrangement will function as a form of a transmission, in that it may be used to vary the angular velocity of the output shaft 230, but at the expense of torque. The combination of the electromagnets 232 and magnets 250 forms a drive means for moving the free member (i.e., rotor shaft 230) with respect to the fixed member (i.e., housing 212).

The actuator 210 may also be provided with an elastic element or spring 252 positioned between the head 246 of rotor assembly 244 and the base 218, as best seen in FIGS. 6, 7, and 10. One end 253 of spring 252 may be fixedly attached to the head 246 of rotor assembly 244, whereas the other end 255 of spring 252 is configured to operatively engage base 218 of actuator 210. A catch assembly 254 may be used to cause the end 255 of spring 252 to engage and disengage from the base 218. More specifically, in the embodiment shown and described herein, the base 218 of actuator 210 may be provided with one or more holes 258 therein that are sized to engage with the end 255 of spring 252. A disk 256 having one or more pins 260 provided therein may be mounted to the housing 12, e.g., by one or more actuators 262 in the manner best seen in FIGS. 6, 7, and 10. The actuators 262 may cause the disk 256 to move toward and away from base 218. When the disk 256 is moved toward base 218, the pins 260 engage the corresponding holes 258 in base 218, ultimately pushing end 255 of spring 252 out of the hole 258, thereby disengaging spring 252 from base 218. Because the pins 260 are flush with the surface of base 218, the end 255 of spring 252 will slide around the base 218 as the head 246 of rotor assembly 244 turns without becoming re-engaged with base 218. However, when the disk 256 is moved away from the base 218, the pins 260 disengage from holes 258, allowing the end 255 of spring 252 to re-engage with one of the holes 258.

The spring 252 thus allows the actuator 210 to store energy in two different manners. First, spring 252 can be compressed between the head 246 and the base 218, thus storing energy. Second, spring can also store energy by being wound up as the head 246 of rotor assembly 244 turns in the manner described herein. Because spring 252 is attached to head 246, the spring 252 is able to store energy both by compression and by winding.

Actuator 210 may also be provided with one or more sensors (not shown) to detect the position of the rotor assembly 244 with respect to the housing 212. It is generally preferred, but not required, that the sensor comprise a non-contact type of sensor to decrease the overall friction load of the system. Exemplary non-contact sensors include optical sensors and magnetic feedback sensors. Optical sensors may require a slotted disk to be affixed to the rotor head 246 or rotor shaft 230 such that light traveling between a source and detector is interrupted as the rotor head 246 moves within housing 212. The interruptions are counted by a processing unit and the rotational speed and position are calculated.

Alternatively, the electromagnets 232 themselves may be used as non-contact sensors. For example, by multiplexing the electromagnet's 232 purpose as an attractive, or repulsive magnet, and as a sensor at a very high rate, the electromagnets 232 can be used to determine the location of the magnets 250 in the rotor head 246. That is, the movement of the magnets 250 past the coils 238 in each electromagnet 232 will cause a measurable back-current to be generated in the coil 238.

Actuator 210 may also comprise a control system 264 operatively connected to each of the electromagnets 232. Control system 264 is used to energize the various electromagnets 232 to cause the rotor assembly to both rotate and move from end-to-end, generally along a helical path in the manner described below.

The control system 264 may comprise any of a wide range of hardware and/or software elements (not shown) suitable for applying an electric current to each of the various electromagnets 232.

Referring now primarily to FIG. 9, the magnetic fields B produced by each electromagnet 232 resembles a dipole and the strength of the field decreases as a function of the inverse of the cube of the distance from the electromagnet 232. This magnetic field B can turn on, off, grow, shrink, and reverse depending on the control of the current energizing the electromagnet 232. In the example embodiment illustrated in FIG. 9, the right electromagnet 232 is energized such that the net magnetic vector B (shown by the arrow) is pointing towards that of the magnet 250 in the rotor head 246. As such, these magnets are opposing and therefore repulsive. This enhances the rotation of the rotor head 246 that is spinning under its own momentum. The magnetic field vector B of magnet 250 is pointing away from the left electromagnet 232, as this electromagnet 232 is passing current that is opposite to that in the right electromagnet 232. The magnet 250 on rotor head 246 is therefore attracted to this electromagnet 232. Thus the rotor 246 would move toward the left hand electromagnet 232 and generate torque.

An exemplary control schedule or methodology for applying electric current to each of the electromagnets 232 is as follows. If one numbers the electromagnets 232 along each helical path 236 from 1 at the bottom to N at the top (the maximum number of electromagnets 232 is not fixed as a longer actuator 210 would require more electromagnets 232), then to compress the spring 252 maximally and extend the rotor shaft or sleeve 230 to its longest length, one would energize the three #1 electromagnets 232 so that they attract the magnets 250 in the rotor head 246. Energizing the three #2 electromagnets 232 to attract the magnets 250 while reversing the current through the #1 electromagnets 232 would cause the rotor head 246 to be repulsed from the #1 electromagnets 232 and move toward the #2 electromagnets. As the rotor head 246 gains momentum, activating #3 electromagnets 232 causes the rotor 246 to move to an intermediate position between electromagnets #2 and #3. Reversing the current in the #2 electromagnets causes them to repel the rotor head

15

magnets **250**. The rotor head **246** then rotates towards the **#3** electromagnets **232**. Thus, to continue rotating/retracting the shaft **230** a staggered progression of electromagnet energizations in which the electromagnet **232** is off, then turning on (attracting), then reversing the current (repelling), then turning off will allow control of the position of the rotor assembly **244**, thus output shaft or sleeve **230**.

This type of control of the electromagnets **232** is possible by using a series of transistors and pulse width controller with programming similar to that of a conventional stepper motor controller. The duty cycle of the electromagnets **232** (i.e. the length of energization time) in this cyclical progression depends on the strength of the electromagnets **232**, the required speed of shaft rotation, the strength of the spring **252**, the momentum of the rotor head **246** and the physical dimensions of the actuator **210**.

To use the electromagnets **232** to sense the position of the rotor head **246**, the control system **264** would have to detect or measure the voltage induced in the electromagnets **232** as the magnets **250** in the head **246** pass nearby. Such a voltage measurement can be made extremely quickly so that the momentum of the rotor head **246** keeps the shaft **230** moving, as the electromagnet **232** is not energized during the sensing operation. A computer (not shown) with an analog to digital conversion/data acquisition device or a programmable integrated circuit with enough input/output channels is capable of providing this control.

The rotor assembly **244** is capable of sliding along the guide member **222** for most of its length. The rotor assembly **244** can move along the guide member **222** by sequential activation of the electromagnets **232** in the manner described herein. In addition, the rotor assembly **244** can also move along the guide member **222** under the influence of energy returned by the spring.

Referring now primarily to FIG. **11(a-c)**, in the neutral position (FIG. **11b**), the spring **252** is at its resting length and exerts no force on the rotor head **246**. Sequentially energizing the electromagnets **232** causes the magnets **250**, thus rotor head **246** to rotate and translate along a helical path described by their arrangement. Both rotation and translation of the rotor head **246** result in storage of elastic potential energy in the spring **252**. See FIG. **11a**. Translation of the rotor head **246** stretches the spring **252**, while rotation of the rotor head **246** will wind the spring **252** around the rotor shaft **230** when the spring **252** is fixed to (i.e., engaged with) the base **218**. At maximum spring extension, the free end of shaft **230** is in the retracted position illustrated in FIG. **11a**.

The spring **252** can be compressed (FIG. **11c**) by applying a tensile force at the end of the shaft **230**, or by reversing the direction of sequential activation of the electromagnets **232**. Either a force applied at the end of the shaft **230** or the force of attraction between the electromagnets **232** and the magnets **250**, or both, can prevent the stretched spring **252** from recoiling to its resting position. Thus, not only can the actuator **210** do work on the spring **252**, but spring **252** can do work on actuator **210**.

High thermodynamic efficiency results from the fact that stored elastic potential energy is used to accelerate and decelerate the rotor assembly **244** instead of electricity.

Intrinsic stability arises because the rotor assembly **244** is free to move within the cylinder housing **212**. Oscillations of the spring **252** reduce transmission of applied forces to the fixed end **214** of the actuator **210**. Electromagnetic forces will damp the oscillations of the spring **252**. Changes in the applied force will automatically result in changes in the position of the rotor assembly **244** (and therefore changes in the energy stored in the spring **252**). The spring **252** will become

16

stiffer (i.e., actuator **210** will become less compliant) when the compressive force increases. Actuator **210** will become more compliant when the compressive force decreases. The actuator **210** therefor exhibits viscoelastic properties.

Having herein set forth preferred embodiments of the present invention, it is anticipated that suitable modifications can be made thereto which will nonetheless remain within the scope of the invention. The invention shall therefore only be construed in accordance with the following claims:

What is claimed is:

1. An actuator, comprising:

a fixed member;

a free member operatively engaged with said fixed member so that said free member is moveable with respect to said fixed member;

a connector member, said connector member engaging said fixed member and said free member so that said connector member is moveable with respect to said fixed member and said free member;

an elastic element operatively associated with said connector member and said free member, said elastic element having a variable compliance; and

means for moving operatively associated with said connector member and said fixed member so that said means for moving moves said connector member with respect to said fixed member, said actuator being operable to store energy in said elastic element without a change in an overall length of said actuator, wherein said means for moving comprises a motor mounted to said fixed member; a lead screw mounted for rotation to said fixed member and operatively connected to said motor so that said motor can rotate said lead screw; and a nut mounted to said connector member and operatively engaged with said lead screw, rotation of said lead screw causing said connector member to move with respect to said fixed member.

2. The actuator of claim 1, wherein changes in the compliance of said elastic element changes a compliance of said actuator.

3. The actuator of claim 2, wherein said elastic element increases a compliance of said actuator with a decrease in a contraction force and wherein said elastic element decreases a compliance of said actuator with an increase in the contraction force.

4. The actuator of claim 1, wherein said means for moving does work on said elastic element.

5. The actuator of claim 1, wherein said elastic element does work on said means for moving.

6. The actuator of claim 1, further comprising a take-up system operatively connected to said elastic element, said take-up system lengthening and shortening an operating length of said elastic element to change a compliance of said elastic element.

7. The actuator of claim 6, wherein said take-up system comprises a spool and a motor operatively associated with said spool.

8. The actuator of claim 7, further comprising a strain sensor operatively associated with said actuator, said strain sensor sensing a strain in said actuator.

9. The actuator of claim 6, wherein said take-up system lengthens or shortens said elastic element during operation of said actuator so that a compliance of said elastic element is changed without halting operation of said actuator.

10. The actuator of claim 1, wherein said free member is moveable with respect to said fixed member along an axis so that said actuator is operable along the axis.

17

11. An actuator, comprising:
 a fixed member;
 a connector member operatively engaged with said fixed member so that said connector member can move with respect to said fixed member;
 a free member operatively engaged with said connector member so that said free member can move with respect to said fixed member;
 a drive system operatively associated with said fixed member and said connector member, said drive system operable to move said connector member with respect to said fixed member, wherein said drive system comprises a motor mounted to said fixed member; a lead screw mounted for rotation to said fixed member and operatively connected to said motor so that said motor can rotate said lead screw; and a nut mounted to said connector member and operatively engaged with said lead screw, rotation of said lead screw causing said connector member to move with respect to said fixed member; and
 an elastic element having a first end and a second end, the first end of said elastic element being connected to said free member, the second end being connected to said connector member.

12. The actuator of claim 11,
 wherein said fixed member comprises a tubular structure and wherein said connector member comprises generally elongate structure sized to be slidably received by the tubular structure of said fixed member.

13. The actuator of claim 12, wherein said free member comprises a tubular structure sized to slidably receive said connector member.

14. The actuator of claim 13, wherein said tubular structures of said fixed member and said free members comprise generally hollow, cylindrically-shaped structures.

15. The actuator of claim 14, wherein said fixed member comprises a slot provided therein and wherein said free member comprises at least one slot provided therein, and wherein

18

said connector member comprises a plurality of pins sized to be slidably received by slots provided in said fixed and free members.

16. An actuator, comprising:
 a fixed member;
 a free member operatively engaged with said fixed member so that said free member is moveable with respect to said fixed member;
 a connector member operatively associated with said fixed member and said free member;
 an elastic element operatively associated with said free member and said connector member, said elastic element having a variable compliance; and
 a drive system operatively connected to said fixed member, said connector member, and said elastic element, said drive system changing a length of said elastic element during operation both in contraction and in extension of said actuator to store energy in said elastic element, said drive system and said elastic element applying a total force to said free member during operation both in contraction and in extension of said actuator that is a sum of a force produced by said drive system and a force produced by said elastic element, wherein said drive system comprises a motor mounted to said fixed member; a lead screw mounted for rotation to said fixed member and operatively connected to said motor so that said motor can rotate said lead screw; and a nut mounted to said connector member and operatively engaged with said lead screw, rotation of said lead screw causing said connector member to move with respect to said fixed member.

17. The actuator of claim 16, wherein the compliance of said elastic element changes during operation of said actuator so that a compliance of said actuator is changed without halting operation.

18. The actuator of claim 17, wherein said elastic element is non-linearly elastic.

* * * * *